



Zebra® 110PAX4™ 170PAX4™

Versatile, 4- and 6-Inch-Wide
OEM Print Engines

PAX4™ print engines deliver superior performance and reliability.


The 110PAX4 and the 170PAX4 print engines are the performance leaders in mission-critical print-and-apply applications. With increased throughput and enhanced connectivity, including wireless and Ethernet, along with all-metal construction and outstanding print quality, PAX4 print engines deliver outstanding value, reliability, and durability.

Better Than Ever for High-Volume Needs

With improved serviceability, faster first-label-out time, and a fully functional real-time clock, the PAX4 print engines deliver what it takes to make print-and-apply solutions super performers. European voltage requirements are now met with the 28V I/O option.

Real-time Connectivity and Control

Reduce downtime and increase productivity. Using advanced ZebraLink Solutions, PAX4 print engines offer instant status alert messages and centralized control, allowing you to troubleshoot quickly and keep production lines moving.



Designed for high-speed, high-throughput applications, both the 110PAX4 (for 4 inch printing) and the 170PAX4 (for print widths up to 6 inches wide) are ideal for print/apply systems including:

- Mission-critical industrial applications
- High-volume product, carton, case, and pallet labeling
- Packaging



110PAX4 170PAX4



Specifications at a Glance*

STANDARD FEATURES

Resolution: 203 dpi/8 dots per mm;
300 dpi/12 dots per mm
Memory: 10 MB DRAM; 2 MB non-volatile Flash
Print methods: Thermal transfer or direct thermal
Print Speed: 12"/305 mm per second (203 dpi)
8"/203 mm per second (300 dpi)
Media Sensors: Transmissive and reflective
Orientation: Right-hand or left-hand
Industrial all-metal construction
10 MB DRAM
2 MB non-volatile Flash Memory
Applicator interface
Multilingual backlit LCD
Enhanced Alert notification—monitors
printhead condition
Multi-level Element Energy Equalizer™ (E3®) for
superior print quality
32-bit 133 MHz RISC processor
Zebra printer driver for Windows® 3.X and
Windows 95/98/NT/2000
Real-time clock

OPERATING CHARACTERISTICS

Environmental (Thermal Transfer)
Operating Temp. 31° F/0° C to 105° F/40° C
Storage Temp. -40° F/-40° C to 160° F/71° C
Operating Humidity: 20% to 95% non-condensing
R.H.
Storage Humidity: 5% to 95% non-condensing R.H.
Electrical
Universal power supply with power-factor
correction 90-264 VAC, 48-62 Hz
Agency Approvals
UL-60950 3rd edition, CAN/CSA-C22.2 No 60950-00
3rd edition, FCC part 15 - Class A, ICES-003,
EN60950, EN55022-Class A, EN61000-6-2, VCCI,
CCC

RELATED PRODUCTS

Options and Accessories
PCMCIA cards
CompactFlash® cards
Linear PCMCIA cards available 8 MB and 32 MB
RFID Ready+
UNICODE
WGLA through Swiss 721
Firmware support for downloadable TrueType™
fonts
PC memory card
Additional fonts available

ZEBRALINK SOLUTIONS

Software
ZebraDesigner™ Pro
ZebraNet™ Bridge Enterprise
ZebraNet Utilities v 7.0
Zebra Universal Driver

Networking

ZebraNet® 10/100 Print Server
ZebraNet Wireless Print Server

Firmware

ZPL® II—Universal language for Zebra printers.
Simplifies label formatting and enables format
compatibility with other Zebra printers.
Web View—Enables you to connect and control
your bar code printer's Web interface using a
common Web browser.
Alert—Printers equipped with ZebraNet print
servers will notify you via any email-enabled,
wired, or wireless device to
minimize downtime.

COMMUNICATIONS AND INTERFACE CAPABILITIES

High-speed bi-directional parallel interface,
Centronics® compatible.
High serial interfaces: RS-232C and RS422 with
DB9F connector
RS-485 multi-drop capability
Configured baud rate (110 to 57.6 kB), parity, data
bits, and stop bits
Applicator interface with DB15F connector

BAR CODE SYMBOLOGIES

Linear bar codes
Codabar, Code 11, Code 39, code 93, Code 128
with subsets A/B/C and UCC Case codes, EAN-
8, EAN-13, Industrial 2-of-5, Interleaved 2-of-5,
IBST-128, Logmars, MSI, Planet Code, Plessey,
POSTNET, Standard 2-of-5, UPC-A, UPC-E, UPC
and EAN 2 or 5 digit extensions

2-Dimensional

Codablock, Code 49, Data Matrix, MaxiCode,
MicroPDF, PDF417, QR Code and TLC 39

FONTS AND GRAPHICS

Fonts and Character Sets

Bitmap fonts A through H and GS symbols are
expandable up to 10 times, height and width
independent
Smooth scalable font Ø (CG Triumvirate™ Bold
Condensed) is expandable dot-by-dot, height
and width independent
Sets: IBM® Code Page 850 International
Characters
Contains UFST® from Agfa monotype Corporation

Graphic Features

Supports user-defined fonts and graphics—
including custom logos

110PAX4†

PRINTER SPECIFICATIONS

Print width: 4.1"/104 mm
Print length:
Maximum non-continuous media: 39"/990 mm
Maximum continuous media: 100"/2540 mm

PHYSICAL CHARACTERISTICS

Width: 9.6"/245 mm
Height: 11.8"/300 mm
Depth: 16.4"/417 mm
Weight: 36.5 lbs./15.6 kg

MEDIA CHARACTERISTICS

Media width (label and liner):
.625"/16 mm to 4.5"/114 mm
Media thickness (label and liner):
.0058"/0.148 mm to 0.010"/0.254 mm

MEDIA TYPES

Continuous, die-cut or black mark

RIBBON CHARACTERISTICS

Outside diameter: 4.0"/101.6 mm O.D.
Standard length: 2,955/900 m
Ratio: Ribbon is recommended to be at least as
wide as media
Ribbon setup: Ribbon wound coated-side out
Core I.D.: 1.0"/25.4 mm I.D. core

170PAX4

PRINTER SPECIFICATIONS

Print width: 6.6"/168 mm
Print length:
Maximum non-continuous media: 39"/990 mm
Maximum continuous media: 150"/3810 mm

PHYSICAL CHARACTERISTICS

Width: 9.6"/245 mm
Height: 11.8"/300 mm
Depth: 18.3"/465 mm
Weight: 35.5 lbs./16.1 kg

MEDIA CHARACTERISTICS

Media width (label and liner):
3.0"/76 mm to 7.1"/180 mm
Media thickness (label and liner):
.003"/.076 mm to .012"/305 mm

MEDIA TYPES

Continuous, die-cut or black mark

RIBBON CHARACTERISTICS

Outside diameter: 4.0"/101.6 mm O.D.
Standard length: 2,955/900 m
Ratio: Ribbon is recommended to be at least as
wide as media
Ribbon setup: Ribbon wound coated-side out
Core I.D.: 1.0"/25.4 mm I.D. core

† Effective March 15, 2005 all 110PAX4 print engines have an RFID Ready option.

* Specifications subject to change without notice. ©2005 ZIH Corp. ZebraLink, ZebraNet, Element Energy Equalizer, ZebraDesigner, and Zebra, E³, ZebraNet, ZPL and ZPL II are registered trademarks of ZIH Corp. All rights reserved. CompactFlash is a registered trademark of SanDisk Corporation. TrueType is a trademark of Apple Computer, Inc. Centronics is a registered trademark of Centronics Data Computer Corporation. Windows is a trademark of Microsoft Corporation. CG Triumvirate is a trademark of Agfa Division, Miles Inc. IBM is a registered trademark of International Business Machines Corporation. UFST is a registered trademark of Agfa Monotype Corporation. All other trademarks are the property of their respective owners.

